

# TL-15 ULI



## BURGLARY TOOL RESISTANT SAFE

By far the most commonly used UL listed safe on the market.



### SAFE TYPE :

Plate (steel) safe.

### CERTIFICATION :

Underwriter Laboratories 15 minutes door attack certification.

### PROTECTION TYPE :

15 minutes door protection against common hand or picking tools, mechanical or portable electric tools, drills and pressure devices.

### BODY CONSTRUCTION :

Made of 1/2" thick high tensile steel.

### DOOR CONSTRUCTION :

Made of 1" thick laminated high tensile steel.

Our 1/2" thick high tensile steel has been approved by Underwriter Laboratories as being as resistant or better than 1" thick hot rolled steel used by many of our competitors. Aside from increasing the inside volume of the safe, using 1/2" thick steel dramatically reduce the weight thus making you save on the freight and installation costs.

### BOLTWORK :

From 3 to 7 plated steel locking bolts (Ø1-3/8").

In order to delay any attacks, our ingenious boltwork design makes multiple attacks necessary. In fact, actually attacking and forcing one bolt will result in driving all the other locking bolts in the opposite direction and will make further attacks even harder.

### TL-15 ULI SAFES ARE EQUIPPED WITH :

- Highly efficient bolt detent system that keeps the bolts retracted when the door is opened and never fails to engage them automatically when the door is closed.
- Superior quality double relocker.
- Drill resistive hard plate.
- Stainless steel push plate.

### STANDARD LOCK :

One ( 1 ) Group 2M S&G 6630 3-Wheel combination lock with spy-proof dial.

### MINIMUM INSIDE DIMENSIONS :

20-5/8" High x 15" Wide.

### AVAILABLE OPTIONS :

- Electronic or 4-wheel combination lock.
- Second electronic or mechanical lock.
- Timelock (for safes 35" high inside and up).
- Complete inner wiring of alarm components.
- Alarm Hole. (Ø1/4")
- Anchoring Holes (included if safe is less than 750 pounds as per UL standards).
- Shelf (Adjustable or Fixed).
- Special Interior (As per customer needs)
- High grade polished stainless steel cladding on inner compartments' doors.

### Recessed Coin Rack :

- One Row: Safe needs to be 22" wide inside.
- Two Rows: Safe needs to be 25" wide inside.
- Three Rows: Safe needs to be 29" wide inside.

