

TRTL-30X6 ULI



BURGLARY TORCH & TOOL RESISTANT SAFE



AVAILABLE OPTIONS :

- Second combination lock.
- Electronic or 4-wheel combination mechanical locks.
- Timelock (for safes 35" high inside and up).
- Alarm Hole. (Ø1/2")
- Shelf (Adjustable or Fixed).
- Special Interior (As per customer needs)
- High grade polished stainless steel cladding on inner compartments' doors.

Recessed Coin Rack :

- One Row: Safe needs to be 22" wide inside.
- Two Rows: Safe needs to be 25" wide inside.
- Three Rows: Safe needs to be 29" wide inside.

SAFE TYPE :

Composite safe.

CERTIFICATION :

Underwriter Laboratories 30 minutes door & body attack certification.

PROTECTION TYPE :

30 minutes door & body protection against Oxy-Fuel torches, common hand or picking tools, mechanical or portable electric tools, grinders, drills and pressure devices.

BODY CONSTRUCTION :

Made of 5-1/2" thick steel and special high resistance concrete.

DOOR CONSTRUCTION :

Made of 5-1/2" thick steel and special high resistance concrete.

BOLTWORK :

From 3 to 7 plated steel locking bolts (Ø1-3/8").

In order to delay any attacks, our ingenious boltwork design makes multiple attacks necessary. In fact, actually attacking and forcing one bolt will result in driving all the other locking bolts in the opposite direction and will make further attacks even harder.

TRTL-30X6 ULI SAFES ARE EQUIPPED WITH :

- Highly efficient bolt detent system that keeps the bolts retracted when the door is opened and never fails to engage them automatically when the door is closed.
- Superior quality double relocker.
- Drill resistive hard plate.
- Stainless steel push plates.

STANDARD LOCK :

One (1) Group 1 S&G 8550 3-Wheel combination lock with spy-proof dial.

MINIMUM INSIDE DIMENSIONS :

20-5/8" High X 15" Wide.